



| ITEM | NO. | PART# | MATERIAL | ITEM | NO. | PART# | MATERIAL |
|------|-----|-------|-----------------------------------|------|-----|-------|--|
| a | 3 | | Insulator, pin type | g | 1 | | Crossarm, 3 5/8" x 4 5/8" x 10'-0" |
| b | 1 | | Pin, pole top, 20" | j | 2 | | Screw, lag, 1/2" x 4" (VC1.12R only) |
| c1 | 2 | | Bolt, machine 1/2" x req'd length | bs | 1 | | Bolt, single upset |
| c2 | 5 | | Bolt, machine 5/8" x req'd length | cm | 1 | | Insulator, spool - 3" |
| d1 | 2 | | Washer, round 1/2" | cu | 2 | | Brace, wood, 36" |
| d2 | 7 | | Washer, square 2" x 2" x 11/16" | ec | 1 | | Bracket, offset neutral (VC1.12R only) |
| d3 | 1 | | Washer, curved 3" x 3" x 11/16" | ek | 8 | | Locknuts |
| f | 2 | | Pin, crossarm, steel, 5/8" x 14" | rp1 | 2 | | Perch Guard 36" |
| rp5 | 1 | | Perch Guard 30" | rp6 | 1 | | Perch Guard Pole Top |
| | | | | rp7 | 2 | | Perch Guard Extenders |

NOTES:

DESIGN PARAMETERS:
2° Maximum

24.9 / 14.4 kV, 3-PHASE
SINGLE PRIMARY SUPPORT, CROSSARM CONST.
SMALL CONDUCTORS

RUS

11/10/08

Rev. A



VC1.11RG