



ITEM	PART #	MATERIAL	QTY	ITEM	PART #	MATERIAL	QTY
a	4310	Insulator, Pin Type	6	n	9363	Bolt, Double Arming 5/8"	3
b	4420	Pin, Offset Pole Top	2	n2	9364	Bolt, Double Arming 3/4"	1
c	9371-6	Bolt, Machine - 1/2"	4	aw	9100	Washer, Double Coil 5/8"	4
c2	9372	Bolt, Machine - 5/8"	3	bs	9376	Upset Bolt - 5/8"	1
d	9098	Washer, Round - 1/2"	4	cm	9471	Insulator, Spool - 3"	1
d2	9091	Washer, Square - 2"X2"	3	cu	2040	Brace, 84" X 24"	4
d3	9091-3-5/8	Washer, Square 3"- 11/16"	8	ek	9094	Locknuts, 1/2"	4
d4	9091-4	Washer, Square 4" -13/16"	2	ek	9096	Locknuts, 5/8"	10
f	4375	Pins, Crossarm Saddle	4	ek	9097	Locknuts, 3/4"	2
g	4090	Crossarm, 10ft	2				

DESIGN PARAMETERS:

1. Maximum Line Angle: 2°

**24.9/14.4kV, 3-PHASE DOUBLE
PRIMARY SUPPORT, CROSSARM
CONST. LARGE CONDUCTOR**

RUS

11/7/2017

REV. A



VC2.20LR