


ITEM	MATERIAL	QTY	ITEM	MATERIAL	QTY
a	Insulator, clamp top	4	aw	Washer, spring, 5/8"	4
c1	Bolt, machine, 1/2" x req'd. length	4	cm	Insulator, spool - 3"	2
c2	Bolt, machine, 5/8" x req'd. length	3	cu	Brace, crossarm, wood, 36"	4
d1	Washer, round - 1/2"	4	da	Clevis, rigid	2
d2	Washer, square, 2" x 2" x 11/16"	14	ek	Locknuts	15
f	Pin, crossarm, steel	6	rp1	Salisbury coverup	16'
g	Crossarm, 3 5/8" x 4 5/8" x 10'-0"	2	rp2	Perch Guard 24"	4
n	Bolt, Double-arming, 5/8"	4	rp5	Perch Guard 30"	2
rp8	Perch Guard Pole Top Cone	1	rp7	Perch Guard Extenders	8
a	Insulator, pin type	2			

Notes:

DESIGN PARAMETERS:  
See TABLE IV

24.9 / 14.4 KV, 3-PHASE  
DOUBLE SUPPORT, NEUTRAL ON CROSSARMS  
SMALL CONDUCTORS

RUS		VC2.51RG
04/19/11		
Rev. B		