



ITEM	PART #	MATERIAL	QTY	ITEM	PART #	MATERIAL	QTY
a	4310	Insulator, Clamp Type	1	o	9368-10	Bolt, Eye, 5/8" x 10"	2
c	9372-10	Bolt, Machine 5/8" x 10"	2	av	3114	Insulated Tap Wire	6'
d	9091	Washer, Square, 2 x 2 11/16"	2	aa	4350	Eye Nut	2
d2	9092	Washer, 3" Curved 11/16"	4	as	2160	Clevis, Swinging	2
f	4420	Offset Pole Top Pin	1	cm	4270	Insulator Spool	2
k	4280	Insulator, Epoxilator - 18.75"	2	ek	9096	Locknuts	6
l	2120	Deadend Shoe	2	rp6	4772	Pole Top Punch Guard	1
p		Connector	4				

Design Parameters:

- Maximum Allowable Longitudinal Load = 5000 lbs. per conductor
- Maximum Line Angle = 5° (See Note)

Note: Maximum line angle may be increased to 15° by installing anchor shackles, item 5801, to (horizontal) eyenuts and installing side guy as required.

24.9/14.4 kV, 1 Phase Primary Double Deadend Guarded

7/17/2017

REV. O



VA6.2RG