



| ITEM | PART # | MATERIAL | QTY | ITEM | PART # | MATERIAL | QTY |
|------|------------|---------------------------------------|-----|------|--------|-------------------------------|-----|
| a1 | 4310 | Insulator, (24.9/14.4 KV) | 8 | n2 | 9364- | Bolt, DA, 3/4" X Req'd Length | 2 |
| a2 | 4311 | Insulator, Clamp Type, (24.9/14.4 KV) | 4 | s | 2155 | Clevis, Rigid | 1 |
| c1 | 9371-6 | Bolt, Machine, 1/2" X 6" | 8 | aw | 9100 | Double Coil Lock Washer, 1/2" | 12 |
| c2 | 9372- | Bolt, Machine, 5/8" X Req'd Length | 2 | bi | 9233 | Pole Gain | 1 |
| d1 | 9098 | Washer, Round, 1/2" | 8 | cu | 2035 | Brace, Crossarm 60"X18" | 4 |
| d2 | 9091-3-5/8 | Washer, Square 3" X 3" X11/16" | 26 | cu2 | 2040 | Brace, Crossarm 84"X24" | 4 |
| d3 | 9092 | Washer, Square 3" X 3" X11/16" Curved | 1 | da | 9472 | Insulator, Spool -4" | 1 |
| d4 | 9091-4 | Washer, Square 4" X 4" X 13/16" | 4 | ek | 9094 | Locknut, 1/2" | 8 |
| f | 4375 | Pins, crossarm saddle | 12 | ek | 9096 | Locknut, 5/8" | 18 |
| g1 | 4120 | Wood Crossarm, 3 5/8"X4 5/8"X8'-0" | 2 | ek | 9097 | Locknut, 3/4" | 4 |
| g2 | 4090 | Wood Crossarm, 3 5/8"X4 5/8"X10'-0" | 2 | rp | 4715 | Salisbury Coverup | 16' |
| n1 | 9363- | Bolt, DA, 5/8" X Req'd Length | 8 | | | | |

DESIGN PARAMETERS:

- Bulletin 1728F-803 Table V (up to 21° for 336.4 ACSR)

NOTES:

- SALISBURY COVER UP TO EXTEND 3' BEYOND EACH CROSSARM.

**DOUBLE SUPPORT ON CROSSARMS
(TANGENT) (LARGE CONDUCTORS)
DOUBLE CIRCUIT PRIMARY
24.9/14.4 kV**

RUS
11/7/2017
REV. C



VD2.91LR